

WORKHORSE" MSA & MSD"

GOODYEAR'S HARDWORKING MIXED SERVICE TIRES FOR LONG MILES TO REMOVAL IN ON- AND OFF-ROAD APPLICATIONS

- MADE STRONGER TO LAST LONGER

 Dependable mixed service compounds help improve miles to removal and cut/chip resistance
- FULLY REINFORCED

 Steel belt casing helps provide excellent retreadability through multiple retread cycles

WORKHORSE MSA

- DIGS IN DEEP
 - Deep 22/32" tread depth enhances toughness and miles to removal (tread depth 23/32" in super single sizes)
- STONES GET STONEWALLED

 Stone protectors help resist stone drilling for retreadability



315/80R22.5 design only



385/65R22.5 & 485/65R22.5 design only

WORKHORSE MSD

- FIGHTS IN THE TRENCHES
 - Deep 31/32" tread with rugged lug configuration enhances traction and miles to removal
- THICK-SKINNED
 - Deep undertread enhances retreadability

Drive







WORKHORSE® MSA AVAILABLE SIZES AND LOAD RANGES


TIRE SIZE LOAD		SINGLE Load		SINGLE Inflation		DUAL LOAD		DUAL Inflation		WEIGHT		RIM WIDTH			OVERALL Diameter		STATIC Radius		RPM	RPK	TREAD Depth	MIN. DUAL Spacing		SPEED
	RANGE	LBS	KG	PSI	KPA	LBS	KG	PSI	KPA	LBS	KG	IN	IN	MM	IN	MM	IN	MM			32NDS	IN	MM	RATING
									TUBELESS	TIRES ON 15	° DROP CENT	ER RIMS												
11R22.5	Н	6,610	3,000	120	830	6,005	2,725	120	830	120	54	8.25	11.0	279	41.7	1,059	19.5	495	498	310	22	12.5	318	68
315/80R22.5	L	10,200	4,625	130	900	9,090	4,125	130	900	142	64	9.00	12.5	318	43.0	1,092	19.9	505	483	300	23	13.8	351	68
385/65R22.5	J	9,370	4,250	120	830	N/A	N/A	N/A	N/A	164	74	12.25	14.9	378	42.5	1,080	19.8	503	488	303	23	N/A	N/A	68
425/65R22.5	L	11,400	5,150	120	830	N/A	N/A	N/A	N/A	182	83	12.25	16.3	414	44.4	1,128	20.6	523	468	291	23	N/A	N/A	68
11R24.5	Н	7,160	3,250	120	830	6,610	3,000	120	830	135	61	8.25	11.0	279	43.7	1,110	20.4	518	475	295	22	12.5	318	68
12R24.5	Н	7,830	3,550	120	830	7,160	3,250	120	830	150	68	8.25	11.3	287	45.1	1,146	21.1	536	461	287	22	13.2	335	68

Check goodyeartrucktires.com for updated data.

Complementary Products

DRIVE

Workhorse MSD



Recommended Applications





315/80R22.5 design only 385/65R22.5 & 485/65R22.5 design only

WORKHORSE® MSD® AVAILABLE SIZES AND LOAD RANGES

TIRE SIZE	LOAD SINGLE LOAD			SINGLE Inflation		DUAL LOAD		DUAL Inflation		WEIGHT		RIM WIDTH	OVERALL WIDTH		OVERALL DIAMETER		STATIC RADIUS		RPM	RPK	TREAD Depth	MIN. DUAL Spacing		SPEED
	RANGE	LBS	KG	PSI	KPA	LBS	KG	PSI	KPA	LBS	KG	IN	IN	MM	IN	MM	IN	MM			32NDS	IN	MM	RATING
									TUBELESS	TIRES ON 15	° DROP CENT	ER RIMS												
11R22.5	Н	6,610	3,000	120	830	6,005	2,725	120	830	129	58	8.25	11.2	284	42.6	1,082	20.0	508	490	305	31	12.5	318	62
11R24.5	Н	7,160	3,250	120	830	6,610	3,000	120	830	137	62	8.25	11.2	284	44.5	1,130	20.9	531	469	291	31	12.5	318	62

Check goodyeartrucktires.com for updated data

Complementary Products

ALL-POSITION

Workhorse MSA G289® WHA®

Recommended Applications





Competitive Replacements									
BFGoodrich Cross Control D	Continental HDC3								
Firestone T831									

To see how Goodyear® tires can help your fleet save money, go to goodyeartrucktires.com.

TOTAL MOBILITY"-





Premier Service Network
Reliable service network of 2,300+
dealer locations nationwide.

Complete Tire Management
Unparalleled programs and tools
to optimize tire assets and ROI.

goodyeartrucktires.com