



RECREATIONAL VEHICLE BROCHURE

GOODYEAR
MORE DRIVEN.

RV TIRES




G670 RV® MRT

SUPERB PERFORMANCE AND HANDLING AND HELPS RESIST WEATHER CRACKING

- ANTI-OXIDANTS AND ANTI-OZIDANT COMPOUNDS help guard against weather cracking
- RUBBER COMPOUNDS enhance traction and treadwear
- CIRCUMFERENTIAL GROOVES enhance wet traction
- NOTCHES AND SIPES enhance dry traction
- HIGH-TECHNOLOGY BELT SYSTEM helps offer ride comfort
- TREAD PATTERN helps produce low heat and strength, and reduces squirm for superb handling
- FUEL-EFFICIENT CASING enhances fuel economy

Recommended Applications



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width		Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	mm	in	mm	in	mm	in	mm				in	mm	
245/75R22.5	G	4,675	2,120	110	760	4,410	2,000	110	760	83.16	37.721	7.50	191	9.5	241	37.0	940	17.3	439	560	348	14	11.0	289	75
255/70R22.5	H	5,510	2,500	120	830	5,070	2,300	120	830	86.35	39.168	7.50	191	10.0	253	36.4	925	17.0	432	566	352	14	11.3	287	75
265/75R22.5	G	5,205	2,360	110	760	4,805	2,180	100	690	93.01	42.189	7.50	191	10.0	254	38.4	975	17.9	455	537	334	14	11.6	295	75
275/70R22.5	H	6,940	3,150	125	860	6,395	2,900	125	860	92.83	42.108	7.50	191	10.4	264	37.6	955	17.4	442	548	341	14	11.9	302	75
275/80R22.5	H	7,160	3,250	125	860	6,610	3,000	125	860	115.96	52.599	8.25	210	11.1	282	40.2	1,021	18.8	478	517	321	18	12.3	312	75
295/80R22.5	H	7,830	3,550	125	860	6,940	3,150	125	860	109.23	49.547	9.00	229	12.1	307	41.3	1,049	19.2	488	499	310	16	13.2	335	75
315/80R22.5	L	9,090	4,125	130	900	8,270	3,750	130	900	132.81	60.243	9.00	229	12.5	318	42.5	1,080	19.8	503	489	304	16	13.8	351	75

LOAD/INFLATION INFORMATION FOR G670 RV MRT

TIRE LOAD LIMITS (LBS) AT VARIOUS COLD INFLATION PRESSURES (PSI) HIGHWAY STEER AND ALL-POSITION TREAD DESIGNS USED IN NORMAL HIGHWAY SERVICE*

Tire Size	Max Speed Rating mph	Single (S) Dual (D)	Inflation Pressure - PSI														
			70	75	80	85	90	95	100	105	110	115	120	125	130		
245/75R22.5	75	S D	3470 3260	3645 3425	3860 3640	3980 3740	4140 3890	4300 4080	4455 4190	4610 4335	4675 (G) 4410 (G)						
255/70R22.5	75	S D			4190 3970	4370 4110	4550 4275	4675 4410	4895 4455	5065 4610	5205 4675	5400 4915	5510 (H) 5070 (H)				
265/75R22.5	75	S D	3875 3525	4070 3705	4300 3860	4440 4040	4620 4205	4805 4410	4975 4525	5150 4685	5205 (G) 4805 (G)						
275/70R22.5	75	S D				5170 4770	5400 4980	5630 5180	5850 5390	6070 5590	6290 5800	6510 6000	6730 6200	6940 (H) 6395 (H)			
275/70R22.5 (G159)	75	S D				4885 4535	5080 4750	5305 4960	5530 5165	5750 5370	5965 5575	6185 5775	6400 5975	6610 (H) 6175 (H)			
275/80R22.5	75	S D					5500 5080	5745 5305	5985 5530	6225 5750	6460 5965	6700 6185	6930 6400	7160 (H) 6610 (H)			
295/80R22.5	75	S D			5480 4855	5750 5100	6020 5335	6285 5570	6550 5805	6810 6035	7070 6265	7320 6490	7580 6720	7830 (H) 6940 (H)			
315/80R22.5	75	S D				6415 5840	6670 6070	6940 6395	7190 6540	7440 6770	7610 6940	7920 7210	8270 7610	8680 7940	9090 (L) 8270 (L)		

*Industry standards for load and inflation are in the process of being revised. These tables are current as of 06/16/17. For the most current information, please visit the RV Tire section of Goodyear's website at www.goodyearrvtires.com.

RV TIRES



G670 RV® ULT

SUPERB PERFORMANCE AND HANDLING AND HELPS RESIST WEATHER CRACKING

- ANTI-OXIDANTS AND ANTI-OZIDANT COMPOUNDS help guard against weather cracking
- RUBBER COMPOUNDS enhance traction and treadwear
- CIRCUMFERENTIAL GROOVES enhance wet traction
- NOTCHES AND SIPES enhance dry traction
- HIGH-TECHNOLOGY BELT SYSTEM helps offer ride comfort
- TREAD PATTERN helps produce low heat and strength, and reduces squirm for superb handling
- FUEL-EFFICIENT CASING enhances fuel economy

Recommended Applications



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width		Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	mm	in	mm	in	mm	in	mm				in	mm	
225/70R19.5	F	3,640	1,650	95	660	3,415	1,550	95	660	57.93	26.277	6.75	171	8.9	226	32.0	813	14.9	378	644	400	13	10.0	254	75
245/70R19.5	G	4,540	2,060	110	760	4,410	2,000	110	760	70.86	32.142	7.50	191	9.7	246	33.0	838	15.3	389	626	389	13	11.0	279	75

LOAD/INFLATION INFORMATION FOR UNISTEEL® G670 RV

TIRE LOAD LIMITS (LBS) AT VARIOUS COLD INFLATION PRESSURES (PSI) HIGHWAY STEER AND ALL-POSITION TREAD DESIGNS USED IN NORMAL HIGHWAY SERVICE*

Tire Size	Max Speed Rating mph	Single (S) Dual (D)	Inflation Pressure - PSI																						
			70	75	80	85	90	95	100	105	110	115	120	125	130										
225/70R19.5	75	S D		2895 2720	3040 2860	3195 3000	3315 3115	3450 3245	3640 (F) 3415 (F)	3715 3490	3845 3615	3970 (G) 3750 (G)													
245/70R19.5	75	S D			3640 3415	3740 3515	3890 3655	4080 (F) 3970 (F)	4190 4115	4335 4265	4540 (G) 4410 (G)														

*Industry standards for load and inflation are in the process of being revised. These tables are current as of 06/16/17. For the most current information, please visit the RV Tire section of Goodyear's website at www.goodyearrvtires.com.

*Tires produced after 2/28/06



G614 RST®

EVEN WEAR IN DEMANDING TRAILER APPLICATIONS

- SHALLOW TREAD offers even wear and helps reduce running temperatures for casing toughness
- SOLID, ROUNDED SHOULDER RIBS enhance rib stability to promote even wear
- PREMIUM CASING is tough and retreadable
- RIB EDGE SIPES AND LATERAL GROOVES help deliver traction

Recommended Applications



Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width		Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	mm	in	mm	in	mm	in	mm				in	mm	
LT235/85R16	G	3,750	1,700	110	750	3,415	1,550	110	750	60.09	27.257	6.50	165	9.5	241	30.7	780	14.4	366	671	417	12	10.8	274	75

LOAD/INFLATION INFORMATION FOR UNISTEEL G614 RST

TIRE LOAD LIMITS (LBS) AT VARIOUS COLD INFLATION PRESSURES (PSI) HIGHWAY STEER AND ALL POSITION TREAD DESIGNS USED IN NORMAL HIGHWAY SERVICE*

Tire Size	Single (S) Dual (D)	Inflation Pressure - PSI																
		35	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	
LT235/85R16	S D	1700 1545	1870 1700	2030 1845	2205 2006	2335 2125	2485 2260	2623 (D) 2381 (D)	2765 2515	2905 2645	3042 (E) 2778 (E)	3170 2885	3300 3005	3415 3085	3550 3230	3675 3345	3750(G) 3415(G)	

*Industry standards for load and inflation are in the process of being revised. These tables are current as of 06/16/17. For the most current information, please visit the RV Tire section of Goodyear's website at www.goodyearrvtires.com.

TRAILER TIRE




GOODYEAR® ENDURANCE®

A DEPENDABLE TRAILER TIRE DESIGNED TO HELP YOU TOW WITH CONFIDENCE

- OPTIMIZED TREAD DEPTH AND DECOUPLING GROOVE help tire to remain cool while towing heavy loads
- RUGGED FABRIC-STEEL CONSTRUCTION offers improved durability and carrying capacity while remaining compatible with tire pressure monitoring systems and typical tire inflation stations
- SPECIALIZED INNER LINER minimizes air loss in trailer applications because of 100% halobutyl rubber
- SCUFF GUARD helps provide sidewall protection
- DURAWALL® TECHNOLOGY helps resist sidewall cuts and punctures

Recommended Applications



Size	Service Description	Load Range	Sidewall	Product Code	Material Number	Approved Rim Width (ins)	Measuring Rim Width (ins)	Section Width (ins)	Overall Diameter (in 32nds)	Max Load (lbs)	Tread Depth (in 3)	Revs/ Mile
ST205/75R14	105N	D	BSW	724864519	232865	5.0 - 6.5	5.5	8.0	26.1	2,040	8	797
ST215/75R14	108N	D	BSW	724865519	232866	5.5 - 7.0	6.0	8.5	26.7	2,200	8	779
ST205/75R15	107N	D	BSW	724861519	232551	5.0 - 6.5	5.5	8.0	27.1	2,150	8	768
ST225/75R15	117N	E	BSW	724857519	231946	6.0 - 7.0	6.0	8.7	28.3	2,830	8	735
ST235/80R16	123N	E	BSW	724858519	231947	6.0 - 7.5	6.5	9.3	30.8	3,420	8	675
ST235/85R16	125N	E	BSW	724860519	231948	6.0 - 7.5	6.5	9.3	31.7	3,640	8	659
ST255/85R16	129N	E	BSW	724862519	231949	6.5 - 8.0	7.0	10.0	33.1	4,080	8	631

LOAD/INFLATION INFORMATION FOR GOODYEAR ENDURANCE SPECIAL TRAILER (ST) TIRES

TIRE LOAD LIMITS (LBS) AT VARIOUS COLD INFLATION PRESSURES (PSI) USED IN NORMAL HIGHWAY SERVICE*

Tire Size	Max Speed Rating mph	Inflation Pressure - PSI													
		25	30	35	40	45	50	55	60	65	70	75	80	95	110
ST205/75R14	87	1170	1300	1430	1530	1640	1760	1850	1950	2040 (D)					
ST215/75R14	87	1270	1410	1520	1660	1790	1870	2010	2120	2200 (D)					
ST205/75R15	87	1220	1360	1480	1610	1720	1820	1940	2040	2150 (D)					
ST225/75R15	87	1430	1600	1760	1880	2020	2150	2270	2380	2540	2620	2720	2830(E)		
ST235/80R16	87	1720	1920	2090	2270	2430	2600	2730	2870	3000	3140	3260	3420(E)		
ST235/85R16	87	1830	2040	2200	2400	2580	2760	2910	3060	3200	3360	3480	3640(E)	3960	4400
ST255/85R16	87	2110	2360	2600	2780	2980	3200	3360	3520	3640	3860	4020	4080(E)		

*Industry standards for load and inflation are in the process of being revised. These tables are current as of 06/16/17. For the most current information, please visit the RV Tire section of Goodyear's website at www.goodyearvtires.com.

POPULAR ALTERNATIVE TIRE SIZES

Some manufacturers use slightly different size designations.

Here are a few popular OE-acceptable RV tire size equivalents:

- 235/80R22.5 = 245/75R22.5
- 255/80R22.5 = 265/75R22.5
- 295/75R22.5 = 275/80R22.5

COMPETITIVE REPLACEMENTS

Goodyear	Michelin/Other
G670 RV MRT	Michelin XRV, X Coach HL Z, Z Multi Z, XZE and X Line Energy Z
G670 RV ULT	Michelin XZE
G614 RST	Michelin XPS Rib
Endurance	Carlisle Radial Trail HD, Kenda Karrier KR03 and King Towmax STR II

