KELLY ARMORSTEEL LHS, LHD & LHT



FUEL EFFICIENCY AND LONG MILES TO REMOVAL



The Kelly Armorsteel LHS, LHD and LHT offer a low cost per mile by balancing fuel efficiency and SmartWay verification with long miles to removal. Better yet, their casings can be retreaded multiple times for even more miles of service. They're also backed by a nationwide limited warranty, so you can choose Kelly Armorsteel long haul tires with confidence.



SmartWay Verified



OFFERING FLEETS A LOW COST PER MILE



Armorsteel LHS[™] Long Haul Steer Tire Offering Enhanced Fuel Efficiency And Long Miles To Removal

many miles to removal



Long Haul



Steer



SmartWay® Verified

| many miles to removal |
|--|
| • Barrel-shaped footprint, edge blades and five-rib design offer even wear, many miles |
| to removal and a low cost per mile |

• Uniquely shaped pressure distribution groove helps minimize shoulder wear for

• The evolving tread pattern encourages uniform wear and exposes angled grooves as the tire wears to enhance traction and handling

| Tire Size | Load | Single Load | | Single Inflation | | Dual Load | | Dual Inflation | | Weight | | Rim Width | Overall Width | | Overall Diameter | | Static Radius | | RPM | RPK | Tread Depth | Min. Dual Spacing | | Speed Rating |
|-------------|--|----------------|-------|---------------------|-----|-----------|-------|-------------------|-----|--------|------|--------------|------------------|-----|---------------------|-------|------------------|-----|-----|-----|----------------|----------------------|-----|-----------------|
| | Range | lbs | kg | psi | kpa | lbs | kg | psi | kpa | lbs | kg | in | | mm | | mm | | mm | | | 32nds | in | mm | hating |
| | TUBELESS TIRES ON 15° DROP CENTER RIMS | | | | | | | | | | | | | | | | | | | | | | | |
| 11R22.5 | G | 6,175 | 2,800 | 105 | 720 | 5,840 | 2,650 | 105 | 720 | 109.7 | 49.8 | 8.25 | 10.8 | 274 | 41.6 | 1,057 | 19.3 | 490 | 499 | 310 | 18 | 12.5 | 318 | 75 |
| 295/75R22.5 | G | 6,175 | 2,800 | 110 | 760 | 6,175 | 2,575 | 110 | 760 | 107.8 | 48.9 | 8.25 | 11.1 | 282 | 40.5 | 1,029 | 18.9 | 480 | 513 | 319 | 18 | 12.9 | 328 | 75 |
| 11R24.5 | G | 6,610 | 3,000 | 105 | 720 | 6,005 | 2,725 | 105 | 720 | 118.2 | 53.7 | 8.25 | 11.0 | 279 | 44.3 | 1,125 | 20.6 | 523 | 469 | 291 | 18 | 12.5 | 318 | 75 |
| 285/75R24.5 | G | 6,175 | 2,800 | 110 | 760 | 5,675 | 2,575 | 110 | 760 | 112.6 | 51.1 | 8.25 | 11.1 | 282 | 41.6 | 1,057 | 19.4 | 493 | 499 | 310 | 18 | 12.5 | 318 | 75 |



Armorsteel LHD Long Haul Drive Tire Offering Enhanced Fuel Efficiency And Long Miles To Removal



- Large, stable blocks help enhance fuel efficiency and even wear
- Four-belt construction helps enhance toughness and tire life
- Circumferential and lateral grooves help deliver all-season traction
- Closed shoulder design helps promote uniform wear throughout the life of the tire



Long Haul



Drive



SmartWay Verified

| Tire Size | Load Range | Single Load | | Single Inflation | | Dual Load | | Dual Inflation | | Weight | | Rim Width | | | Overall Diameter | | Static Radius | | RPM | RPK | Tread Depth | | | Speed Rating |
|-------------|--|----------------|-------|---------------------|-----|-----------|-------|-------------------|-----|--------|------|--------------|------|-----|---------------------|-------|------------------|-----|-----|-----|----------------|------|-----|-----------------|
| | | lbs | kg | psi | kpa | lbs | kg | psi | kpa | lbs | kg | in | in | mm | in | mm | in | mm | | | 32nds | in | mm | |
| | TUBELESS TIRES ON 15° DROP CENTER RIMS | | | | | | | | | | | | | | | | | | | | | | | |
| 295/75R22.5 | G | 6,175 | 2,800 | 110 | 760 | 5,675 | 2,575 | 110 | 760 | 118.2 | 53.7 | 8.25 | 11.1 | 282 | 40.9 | 1,039 | 19.3 | 490 | 510 | 317 | 26 | 12.9 | 328 | 75 |



Armorsteel LHTLong Haul Trailer Tire Offering Enhanced Fuel Efficiency And Long Miles To Removal

- Mono-groove tread design helps promote even wear and helps evacuate water from the tread for enhanced wet traction
- Unique center groove design helps resist stone drilling and cracking
- Low tread void helps provide long mileage, enhanced braking and even wear
- Decoupling groove helps minimize shoulder wear for many miles to removal

Long Haul



Trailer



SmartWay Verified

| Tire Size | Load | Single Load | | Single Inflation | | Dual Load | | Dual Inflation | | Weight | | Rim Width | | | Overall Diameter | | Static Radius | | RPM | RPK | Tread Depth | | Dual cing | Speed Rating |
|-------------|--|----------------|-------|---------------------|-----|-----------|-------|-------------------|-----|--------|------|--------------|------|-----|---------------------|-------|------------------|-----|-----|-----|----------------|------|--------------|-----------------|
| | Range | lbs | kg | psi | kpa | lbs | kg | psi | kpa | lbs | kg | in | in | mm | in | mm | in | mm | | | 32nds | in | mm | nating |
| | TUBELESS TIRES ON 15° DROP CENTER RIMS | | | | | | | | | | | | | | | | | | | | | | | |
| 11R22.5 | G | 6,175 | 2,800 | 105 | 720 | 5,840 | 2,650 | 105 | 720 | 103.1 | 46.8 | 8.25 | 10.9 | 277 | 41.3 | 1,049 | 19.2 | 488 | 499 | 310 | 13 | 12.5 | 318 | 75 |
| 295/75R22.5 | G | 6,175 | 2,800 | 110 | 760 | 5,675 | 2,575 | 110 | 760 | 98.2 | 44.6 | 8.25 | 11.1 | 282 | 40.0 | 1,016 | 18.7 | 475 | 515 | 320 | 13 | 12.9 | 328 | 75 |
| 11R24.5 | G | 6,610 | 3,000 | 105 | 720 | 6,005 | 2,725 | 105 | 720 | 113.5 | 51.5 | 8.25 | 11.0 | 279 | 43.3 | 1,100 | 20.2 | 513 | 476 | 296 | 13 | 12.5 | 318 | 75 |
| 285/75R22.5 | G | 6,175 | 2,800 | 110 | 760 | 5,675 | 2,575 | 110 | 760 | 104.6 | 47.5 | 8.25 | 11.1 | 282 | 41.3 | 1,049 | 19.3 | 490 | 499 | 310 | 13 | 12.5 | 318 | 75 |

www.kellytires.com/truck

