

KELLY[®]

ARMORSTEEL MSA & ARMORSTEEL MSD



MIXED SERVICE TIRES FOR ALL-AROUND
ON- AND OFF-ROAD PERFORMANCE



The Kelly Armorsteel MSA and Armorsteel MSD offer toughness to help your fleet get the job done. Both tires offer durable tread compounds and casings that help resist cuts, punctures and excessive wear, and help minimize downtime. This strength results in a long original tread life plus retreadability.

KELLY  **TIRES**[™]

ON- AND OFF-ROAD PERFORMANCE



Armorsteel MSA

Mixed-Service All-Position Tire
For On- And Off-Road



- **Optimized tread compound** helps resist cuts and chips for enhanced toughness, long original tread life and retreadability
- **Enhanced casing construction** helps resist cuts and punctures to promote casing toughness
- **Tread groove stone ejectors** help prevent stone trapping and drilling to enhance casing toughness and retreadability
- **Four steel-belt package** enhances retreadability

Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width		Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	mm	in	mm	in	mm	in	mm				in	mm	
TUBELESS TIRES ON 15" DROP CENTER RIMS																									
11R22.5	H	6,610	3,000	120	830	6,005	2,725	120	830	110	50	8.25	11.0	279	41.5	1,054	19.2	488	501	311	20	12.5	318	68	
11R24.5	H	7,160	3,250	120	830	6,610	3,000	120	830	118	53	8.25	11.2	284	43.5	1,105	20.3	516	478	297	20	12.5	318	68	



Armorsteel MSD

Special Service Drive Tire Designed Primarily For Off-Road Service Combined With Heavy On-Road Use



- **Aggressive tread pattern** with wide lateral grooves improves off-road traction
- **Deep tread** helps provide increased mileage and long wear
- **Specialized tread compound** helps increase treadwear without sacrificing resistance to cuts and abrasions
- **Shoulder tie bars** add stability to improve handling and help prevent irregular wear

Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width		Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth 32nds	Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	mm	in	mm	in	mm	in	mm				in	mm	
TUBELESS TIRES ON 15" DROP CENTER RIMS																									
11R22.5	H	6610	3000	120	830	6005	2725	120	830	141	64	8.25	10.9	277	42.0	1067	19.8	503	497	309	28	12.5	318	75	
11R24.5	H	7160	3250	120	830	6610	3000	120	830	150	68	8.25	10.9	277	44.0	1118	20.8	528	474	295	28	12.5	318	75	

www.kellytires.com/truck

KELLY TIRES™