

Kelly® Commercial Truck Tires

With a heritage of value, performance and dependability, Kelly commercial tires have represented A Good Deal On a Great Tire! The same applies today – Kelly tires can deliver great tread life and performance. Kelly casings can be retreaded multiple times for additional miles of service and have a wide range of KLS steer/all-position, KDA drive and KTSA trailer sizes to help get you where you want to go. Kelly commercial tires are also backed by a nationwide limited warranty to give you peace of mind and confidence.



KLS™
Steer/All-Position

KDA®
Drive

KTSA®
Trailer





KLS™ Steer/All-Position



- 18/32" tread depth and five-rib construction offer even wear and many miles to removal.
- Lateral grooves and rib edge sipes help enhance traction in wet, icy and snowy conditions.
- Tread compound for long haul steer applications offers great handling and many miles to removal.
- Pressure distribution grooves help promote even wear and tear resistance.

Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width		Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth		Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	in			mm	32nds	in	mm	
TUBELESS TIRES ON 15" DROP CENTER RIMS																										
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	119	54	8.25	10.8	274	41.2	1,046	19.2	488	504	313	18	12.5	318	75		
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	110	760	114	52	8.25	11.1	282	40.2	1,021	18.8	478	517	321	18	12.9	328	75		
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	127	58	8.25	10.8	274	43.2	1,097	20.1	511	481	299	18	12.5	318	75		
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	110	760	117	53	8.25	11.1	282	41.3	1,049	19.4	493	503	313	18	12.5	318	75		



KDA® Drive




- Unique shoulder design helps promote traction and uniform treadwear.
- Deep 28/32" tread depth helps provide long original tread life.
- Tread radius helps distribute pressure evenly over the footprint for uniform treadwear and long tread life.
- Stone ejectors help resist casing damage.
- Unique blading pattern enhances the performance and appearance as the tire begins to wear.
- All-steel casing and belts enhance toughness and help increase casing life.

Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width		Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth		Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	in			mm	32nds	in	mm	
TUBELESS TIRES ON 15" DROP CENTER RIMS																										
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	125	57	8.25	10.9	277	42.0	1,067	19.5	495	497	309	28	12.5	318	75		
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	100	690	123	56	8.25	11.1	282	40.8	1,036	18.9	480	512	318	28	12.9	328	75		
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	133	61	8.25	10.9	277	44.1	1,120	20.5	521	473	294	28	12.5	318	75		
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	100	690	124	56	8.25	11.0	279	42.0	1,067	19.5	495	496	308	28	12.5	318	75		



KTSA® Trailer



- Mono-groove tread design helps promote even wear and helps evacuate water from the tread for enhanced wet traction.
- Unique center groove design helps resist stone drilling and cracking.
- Low tread void helps provide long mileage, enhanced braking and even wear.
- Decoupling groove helps minimize shoulder wear for many miles to removal.
- Penetration protectors help resist cuts and punctures to enhance retreadability.

Tire Size	Load Range	Single Load		Single Inflation		Dual Load		Dual Inflation		Weight		Rim Width		Overall Width		Overall Diameter		Static Radius		RPM	RPK	Tread Depth		Min. Dual Spacing		Speed Rating
		lbs	kg	psi	kpa	lbs	kg	psi	kpa	lbs	kg	in	in	mm	in	mm	in	mm	in			mm	32nds	in	mm	
TUBELESS TIRES ON 15" DROP CENTER RIMS																										
11R22.5	G	6,175	2,800	105	720	5,840	2,650	105	720	112	51	8.25	10.9	277	41.1	1,044	19.1	485	502	312	13	12.5	318	75		
295/75R22.5	G	6,175	2,800	110	760	5,675	2,575	100	690	105	48	8.25	11.2	284	39.8	1,011	18.5	470	518	322	13	12.9	328	75		
11R24.5	G	6,610	3,000	105	720	6,005	2,725	105	720	116	52	8.25	10.9	277	43.1	1,095	20.0	508	478	297	13	12.5	318	75		
285/75R24.5	G	6,175	2,800	110	760	5,675	2,575	100	690	107	48	8.25	11.0	279	40.9	1,039	19.0	483	504	313	13	12.5	318	75		